


Model SA-2N4

Gas Detection System

Toxic Gases - Oxygen Deficiency - Volatile Organic Compounds
Combustible Gases - Refrigerants



Stand Alone Gas Detection System

Model SA-2N4 standalone gas detection systems are designed to detect and monitor a wide variety of gases in ambient air. System capacity is 1-2 Smart Sensor Modules. Detection is via diffusion. Gas type and range of sensitivity are determined by installing application specific Model SA1 smart sensor modules. User interface is via intuitive full script color LCD. System status is indicated by screen color; green normal no alarm condition, amber alert level 1, red alert level 2 and blue to indicate a fault condition. User interface is non-intrusive using a programming magnet and front panel push button switches. The system controller and the sensors are mounted in a rugged NEMA 4X weatherproof enclosure suitable for installation in non-hazardous locations.

Specifications¹

System	
Detector Type	Model SA1 Smart Sensor Module
Detection Method	Diffusion
Indicator	Color LCD
User Interface	Magnet and front panel switches
Mechanical	
Mounting Dimensions	8.0" W, 10.0" H, 4.00" D 203mm W, 254mm H, 101mm D
Warranty	
System Warranty	2 Years
Detector Warranty	Smart sensor dependent

Electrical	
Input Voltage Range	10 to 30 VDC 90 to 240 AC
Power Consumption	2.5 - 10 watts (sensor dependent)
Serial Output	RS-485 MODBUS RTU
Alarm Relays	2 form "C", 5 amp contacts
Area Classification	Non-hazardous locations NEMA 4X weatherproof
Environmental	
Humidity Range	-40°C to +60°C; -40°F to 140°F
Temperature Range	15% to 95% RH non-condensing

¹ Specifications subject to change without notice

² Visit www.safeguardanalytics.com for a full list of gas sensor options