

Model SA2-HCL (Hydrogen Chloride) Smart Sensor Modules



Description

Model SA2-HCL smart sensor modules are designed to detect and monitor hydrogen chloride gas in ambient air. The modules consist of an electrochemical gas detection sensor and a microprocessor signal conditioning circuit. The signal conditioning circuits includes embedded temperature compensation and advanced detector analytics. Both are housed in a metallic enclosure fitted with gold plated connecting pins. The “Smart Sensor Module” is factory programmed for a specific range of sensitivity. On power up gas type, measurement range and previous zero and span calibration data points are read by the transmitter facilitating a fully automated startup. When used with any of Safeguard Analytics gas detection transmitters calibration may be performed on site or remotely and transported to the point of installation pre-calibrated and ready for operation.

Specifications ¹

Sensor Technology	Electrochemical	Input Voltage (Direct)	3.0 to 3.6 VDC
Detection Method	Diffusion	Power Consumption	10 milliwatts
Sensitivity Options	0-1 ppm to 0-200 ppm	Signal Output	I ² C Protocol
Response Time	T90 less than 90s	Temperature Range	-40°C to +55°C
Accuracy	± 2% of full scale	Humidity Range	15% to 95% non-condensing
Zero Baseline Shift	< 1% of full scale (-30°C to +50°C)	Pressure Range	1 atmosphere ± .1 atm
Span Drift	< 5% signal loss per year	Warranty	2 Years

¹Specifications subject to change without notice.

*Power consumption is sensor dependent

Order Guide

Model SA2-HCL-005	0-5.00 ppm (50 ppb MDL)	Model SA2-HCL-050	0-50.0 ppm (.5 ppm MDL)
Model SA2-HCL-010	0-10.0 ppm (0.1 ppm MDL)	Model SA2-HCL-100	0-100 ppm (1 ppm MDL)
Model SA2-HCL-020	0-20.0 ppm (0.2 ppm MDL)	Model SA2-HCL-200	0-200 ppm (2 ppm MDL)